

21W LED DRIVER



■ FEATURES

| | |
|--------------|-----------|
| Efficiency | 87.0% min |
| Standby loss | 1W Max |
| Protection | OVP,SCP |
| Flicker | 5% Max |
| Efficiency | 87% Min |
| Power Factor | 0.9 Min |

■ Electrical Specifications

| | |
|----------------------|-------------------------------|
| Input Voltage | 230Vac(180-264Vac min/max) |
| Frequency | 50/60HZ Nom (47-63Hz min/max) |
| Input Current | 0.1A±5% |
| Output Voltage | DC:50-80V |
| Output Current | DC:275mA±5% |
| Maximum Output Power | 21.2W |

■ Environmental Specifications

| | |
|-----------------------|--|
| Operating Temperature | 0°C ~ 40°C |
| Storage Temperature | -20°C ~ 70°C |
| Humidity, Operation | 10~90% RH |
| Humidity, Storage | 5~90% RH |
| MTBF(MIL-HDBK-217F) | 50K hrs min.at 240Vac, rated load 25°C |
| | |
| | |

■ Safety and Compliance

| | |
|----------------------|-------------------------------------|
| Safety Requirement | EN61347-1, EN61347-2-13, |
| EMI Requirement | EN55015, GB17743-2007 /CISPR15:2005 |
| Immunity requirement | |
| ESD test | IEC 61000-4-2 |
| EFT test | IEC 61000-4-4 |
| DIP test | IEC 61000-4-11 |
| Surge test | IEC 61000-4-5 |
| | |

■ Dimensions: mm

44mm*21mm*19mm Max

